

EJOT TSSD®

The fastening element for lightweight design

The EJOT TSSD® (thermal adhesive bonding boss / German: Thermischer Stoff-Schluss-Dom) has been developed including the appropriate joining process, in order to realise fastening options for lightweight material. The process is suitable for sandwich elements with hollow core and foam core structures with different top layers preferably with fibre content. The TSSD® can be used as a screw boss for the DELTA PT® screw, or directly as fastening element.



EJOT TSSD®
Ø 9 x 12


EJOT TSSD®
Ø 12 x 13

EJOT TSSD®
with ball head

Standard based on PA6- or PP-matrix

TSSD® installation process

During the joining process, a thermoplastic boss is installed into the plastic component with a defined rotation speed and axial load. The installation can be done with or without a pilot hole, depending on the component material. Due to the applied axial load the fastening element penetrates the component and the frictional heat caused by the rotation causes a partial fusing of the joining parts. After a brief cooling time a thermal adhesive bond and / or mechanical and form-fit occurs, depending on the material.



Application examples



Paper honeycomb + PUR GF top layer
Pull-out force 900 N



Aramid honeycomb + Aramid fibre top layer
Pull-out force 700-1,200 N



PP honeycomb + PP GF top layer
Pull-out force 800 N



PUR foam + 0.6mm Aluminium AW3003
Pull-out force 800 N



Rohacell foam + CRP top layer
Pull-out force 1,300-1,700 N



XPS-foam + PS GF top layer
Pull-out force 500 N



EPP foam + PP GF top layer
Pull-out force 500-900 N



PP GF Foam + PP GF top layer
Pull-out force 1,900 N

For more information please contact Niko Müller, phone +49 2751 529-5959, e-mail nmueller@ejot.de